

Atty. Docket No. 155696-0024  
Express Mail Label No. EK341754940US

UNITED STATES PATENT APPLICATION

FOR

LOW FREQUENCY CATARACT FRAGMENTING DEVICE

INVENTORS:

Alex Urich  
Michael Curtis

PREPARED BY:

IRELL & MANELLA LLP  
840 Newport Center Drive  
Suite 400  
Newport Beach, California 92660  
(949) 760-0991

## BACKGROUND OF THE INVENTION

### 1. Cross-Reference to Related Application

The present application claims benefit of U.S.  
Provisional Application No. 60/173,829, filed December 30,  
5 1999.

### 2. Field of the Invention

The present invention relates to a control circuit for  
driving a transducer that is coupled to a mechanical  
cutting element.

### 3. Prior Art

The lens of a human eye may develop a cataracteous  
condition which affects a patients vision. Cataracteous  
lenses are sometimes removed and replaced in a procedure  
commonly referred to as phacoemulsification. Phaco  
15 procedures are typically performed with an ultrasonically  
driven handpiece which is used to break the lens. The  
broken lens is removed through an aspiration line that is  
coupled to the handpiece.

The handpiece has a tip which is inserted through an  
20 incision in the cornea. The handpiece typically contains a

number of ultrasonic transducers that convert electrical power into a mechanical oscillating movement of the tip. The distal end of the tip has an opening which is in fluid communication with the aspiration line. The oscillating movement of the tip will break the lens into small pieces that are then drawn into the aspiration line through the tip opening.

The handpiece is typically connected to a console that contains a power supply. The power supply provides a driving signal that drives the ultrasonic transducers. To obtain a maximum response from the ultrasonic transducers, the frequency of the driving signal is typically at, or close to, the natural frequency of the transducers. A driving signal at the natural frequency will cause the transducers to operate in a resonant mode.

It has been found that an ultrasonically driven tip will generate heat which may burn or otherwise denature the corneal tissue. The denatured tissue may affect the patients vision. Additionally, the oscillating tip creates turbulence in the surrounding fluid. The turbulent fluid can make it difficult to view the end of the tip and increase the difficulty of performing the procedure. It



BRIEF SUMMARY OF THE INVENTION

One embodiment of the present invention is a control circuit that provides a driving signal to a transducer coupled to a mechanical cutting element. The transducer is  
5 capable of operating in a resonant mode. The driving signal contains a plurality of pulses provided in a time interval that does not cause the transducer to operate in the resonant mode.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is an illustration of an embodiment of a tissue cutting system of the present invention;

Figure 2 is a schematic of a control circuit of the  
5 system;

Figure 3 is a graph showing a driving signal provided by the control circuit; and,

Figure 4 is schematic of an alternate embodiment of a tissue cutting system.

004040 0782450

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

In general the present invention provides a control circuit that provides a driving signal to a transducer that is coupled to a mechanical cutting element. The driving  
5 signal has a waveform such that the mechanical cutting element can cut tissue without generating heat. The driving signal contains packets of pulses separated by pauses. Each packet will have a time duration that does not induce a resonant mode of operation for the transducer.  
10 The packets do have enough energy to move the cutting element and cut tissue. It has been found that the short duration of pulses will cut tissue without generating any significant amount of heat at the cutting site.  
15 Additionally, when used in a fluid environment such as a phaco procedure it was found that the cutting element did not create as much fluid turbulence than devices of the prior art. The reduction in turbulence improves visibility for the surgeon performing the procedure.

Referring to the drawings more particularly by  
20 reference numbers, Figure 1 shows an embodiment of an ultrasonic tissue cutting system 10 of the present invention. The system 10 may include an ultrasonically

driven handpiece which has a tip 14 that can be inserted into a cornea 16. The tip 14 may also be referred to as a cutting element. The handpiece 12 may include one or more ultrasonic transducers 18 that convert electrical power into mechanical movement of the tip 14. The handpiece 12 is typically held by a surgeon who performs a surgical procedure with the system 10. By way of example, the system 10 can be used to perform a phacoemulsification procedure to break and aspirate a lens of the cornea 16.

The handpiece 12 is coupled to a pump 20 by an aspiration line 22. The pump 20 creates a vacuum pressure within the aspiration line 22. The aspiration line 22 is in fluid communication with an inner channel 24 and opening 26 in the tip 14. The vacuum pressure within the line 22 can aspirate matter from the cornea 16.

The system 10 may include a control circuit 28 that provides a driving signal to the transducers 18. The control circuit 28 may be located within a console 30 that is connected to the handpiece 12. The console 30 may have input knobs or buttons 32 that allow the surgeon to vary different parameters of the system 10. The console 30 may



also have a readout display 34 that provides an indication of the power level, etc. of the system 10.

Figure 2 shows an embodiment of a control circuit 28. The control circuit 28 may include a microprocessor 36 that defines the driving signal provided to the transducers 18. The driving signal may be defined in accordance with a software and/or firmware of the system. The processor 36 may be connected to, or contain, memory 38 which contains instructions and data used to perform software to define the driving signal and operate the system 10. Although a microprocessor 36 is shown and described, it is to be understood that other elements, circuits or devices may be used to generate the driving signal.

The processor 36 may be connected to, or contain, a digital to analog (D/A) converter 40. The D/A converter 40 converts digital bits strings provided by the processor 36 to an analog signal. The D/A converter 40 may be connected to a voltage controlled oscillator (VCO) 42 that converts the analog signal to a driving signal. The frequency of the driving signal is dependent upon the amplitude of the analog signal provided from the D/A converter 40. The

driving signal may be amplified by an amplifier 44 before being provided to the transducers 18.

The transducers 18 have a natural frequency.

Additionally, the transducers 18 are capable of operating

5 in a resonant mode to provide a maximum output. The handpiece 12 may also include a horn (not shown) that mechanically amplifies the output of the transducers 18.

Figure 3 shows an example of a driving signal provided to the transducers. The driving signal may include packets of pulses separated by pauses. Each packet may have a duration short enough so that the transducers 18 do not enter a resonant mode of operation. The pulses still have enough energy to induce functional movement of the tip 14. The pauses should be of a duration to avoid resonant operation and the generation of a significant amount of heat.

For phaco handpieces with ultrasonically driven piezoelectric transducers it was found that a packet duration between 0.5-5.0 milliseconds allows the tip to effectively cut tissue without generating a significant amount of heat at the cutting site. Additionally, it was

3.5-50

C found that a pause duration between 5-50 milliseconds provided satisfactory results.

When a phaco handpiece was tested using the above ranges, it was found that the temperature at the cutting  
5 site did not rise above 45 °C. The best results occurred with a packet duration of 0.5 milliseconds and a pause duration of 3.5 <sup>milliseconds</sup> ~~seconds~~ for a repetition frequency of 250 hertz (Hz). Because the transducers 18 do not resonate, the effective oscillation frequency of the transducers 18 and accompanying tip 14 is equal to the repetition frequency.

It is desirable to provide a pulse frequency that is the same or close to the natural frequency of the transducers. For example, for transducers with a natural  
15 frequency of 20 KHz, it was found that a pulse frequency of 22 KHz provided satisfactory results. In general it has been found that providing short packets of pulses that do not induce resonance in the transducers provides a cutting tool that can cut tissue without generating a significant  
20 amount of heat.

While certain exemplary embodiments have been described and shown in the accompanying drawings, it is to be

understood that such embodiments are merely illustrative of  
and not restrictive on the broad invention, and that this  
invention not be limited to the specific constructions and  
arrangements shown and described, since various other  
5 modifications may occur to those ordinarily skilled in the  
art.

For example, Figure 4 shows the present invention  
implemented into a microkeratome 50. The microkeratome 50  
is typically used to cut a flap in the cornea to perform a  
LASIK procedure. LASIK procedures can correct vision by  
10 ablating corneal tissue with a laser.

The microkeratome 50 includes a blade 52 that is  
mounted to a blade holder 54. The blade holder 54 is  
coupled to a motor 56 that can move the blade 52 across a  
cornea. The blade 52 may also be connected to transducers  
15 58 that are connected to a control circuit 60. The control  
circuit 60 may provide a driving signal that causes the  
blade 52 to move in an oscillating manner. The oscillating  
motion of the blade 52 will cut tissue while the motor 56  
20 moves the blade across a cornea. The driving signal may be  
the same or similar to the signal described above and shown  
in Fig. 3. Such a driving signal will allow the blade 52

to cut without generating heat within the tissue. The generation of heat may denature the cornea and affect the patients vision.

Additionally, the control circuit and resultant driving  
5 signal can be used to drive other tissue cutting devices.

004040 032458